

Converting a microPod from wiTECH 2.0 to Enhanced DRB III Emulator

300 Emil Ghiurau Mon, Jul 2, 2018 [wiTECH 2 Public Articles](#) 0 3738

DESCRIPTION

As of **April 28, 2016**, due to new registration requirements, a microPod device will no longer be compatible with wiTECH 1.0 after it is registered with wiTECH 2.0.

Once a device is registered for wiTECH 2.0, it can no longer be converted to be used with wiTECH 1.0 again. We highly recommend assigning a dedicated microPod device to be used with wiTECH 1.0 when needed.



wiTECH 2.0 Device Setup & Configuration:

Due to new registration requirements, a microPOD device will no longer be compatible with wiTECH 1.0 after it is registered with wiTECH 2.0.

Once a device is registered for wiTECH 2.0, it can no longer be converted to be used with wiTECH 1.0 again. We highly recommend assigning a dedicated microPOD device to be used with wiTECH 1.0 when needed.

To setup your microPOD device with wiTECH 2.0, click "Continue".

To configure the wireless settings on a microPOD device to use with wiTECH 2.0, click "Wireless Configuration".

Continue

Wireless Configuration

microPod II devices are a cost effective diagnostic solution for your dealership. We strongly recommend that your dealership purchases an adequate number of microPods for your technicians. To purchase additional microPods, you can login to www.witechsystem.com and go to Order Products >Begin Shopping>wiTECH Products>wiTECH Diagnostic Extender microPod II.

Reminder: FCA highly recommends that every dealership has at least one microPod dedicated for use with Enhanced DRB III Emulator.

Online URL: <https://kb.e.fcawitech.com/article/converting-a-micropod-from-witech-2-0-to-enhanced-drb-iii-emulator-300.html>